



Industrial Line

Svernisolv Gel spray

Technical data sheet
n° 633 Rev. 03/07/2014

Category:

- Special products

Applications:

- Removes most paints

Advantages:

- Efficacy
- Easy spray use

Product for professional use. The manufacturer declines all responsibility for any damage caused by an improper use of the product.

Neutral paint stripper for wood, metals, and any type of surface

Applications

Svernisolv Gel Spray is a neutral paint stripper, applicable on all metals, wood and any type of surface.

The practical gel formulation allows an easy and safe use as it adheres to the surfaces without dripping.

It does not contain chlorinated or aromatic solvents and is completely biodegradable.

Effective on synthetic, nitro, acrylic, urethane, polyesters, and epoxy paints. Excellent also on aluminium and alloys.

It does not contain acidic or alkaline compounds.

It does not contain methylene chloride, trichloroethylene, or aromatic solvents.

Method of Use

Spray a thick layer of product evenly over the surfaces to be treated, from a distance of about 15-20 cm.

Let it work for a few minutes and then remove the paint residues. If necessary, repeat the application.

The product can be detrimental for some types of plastic surfaces. It is advisable to try it on a small surface to check its compatibility with the support to be treated.

Yield: With the 400 ml canister from 8 to 16 m² can be treated depending on the type of surface.

Fields of application

Due to its versatility and ease of use, Svernisolv Gel Spray can be used indifferently in both domestic and professional sectors.