

SOLIC

Technical Sheet n° 184 Rev. 01/07/2014

Mastic-melting solvent for removing glues and silicone

APPLICATIONS:

Solic has been specifically developed to remove silicone and mastic, both fresh and hardened, from metals, glass, wood, ceramic and other hard coatings.

Solic penetrates, inflates and detaches the reticulated resin, allowing its easy removal from surfaces.

The speed of action of the product depending on the type of resin to remove and, thus, it can vary: on single component (urethane, vinyl, acrylic) product, Solic acts in a few minutes; on bi-component or silicone products it normally acts in a longer time.

Given its high aggressiveness on resins, Solic can damage varnished surfaces and other types of plastics. In case of doubt, carry out a preliminary test on the surface to be treated.

METHOD OF USE:

First of all remove the mastic in excess (where possible) with a spatula or a blade.

Apply on the product and wait a few minutes, then remove all with a brush or with a cloth.

If necessary, repeat the operation. Use preferably at room temperature.

FIELDS OF APPLICATION:

- mechanical sector
- chemical sector
- artisan laboratories
- installers of windows and glasses
- Do it yourself

TECHNICAL CHARACTERISTICS

Aspect	Liquid
Odor	Solvent
Colour	Colourless
Density (20°C)	0,880 g/cm3