



Industrial Line

Pneolube

Technical data sheet
n° 674 Rev. 13/05/2014

Category:

- Lubricants for industry

Applications:

- Lubricates hydraulic systems

Advantages:

- Available in various viscosity grades

Product for industrial/professional use. The manufacturer declines all responsibility for any damage caused by an improper use of the product.

Special lubricant mineral oil for hydraulic fluid and hydraulic systems

Applications

Pneolube is an anti-wear oil for hydraulic fluid controls particularly suitable for hydraulic circuits and hydrostatic lubrication systems working under severe conditions due to operating pressure and temperature.

It is widely used for the lubrication of various parts of industrial machinery such as bearings, cylindrical and tapered gears, hydraulic power units, lubrication of lathe power heads.

It is formulated with strictly refined paraffinic mineral bases and with a specific package of selected additives.

Available in the following ISO grades: 32, 46, 68, 100, 150.

Method of Use

Use is recommended for all hydraulic systems, both in normal and heavy conditions.

Moreover, Pneolube maintains the circuits, in which it is contained, free from moisture and protected from oxidation.

The product does not damage the rubber parts (Viton, etc.) of the gaskets.

Technical features

Appearance:	liquid
Colour:	Dark yellow - brown
ISO Viscosity	32, 46, 68, 100 e 150
Odour:	petroleum fraction
Density at 15°C:	0.87 – 0.89
Water-soluble:	no