



Industry Line

HB 180

Technical sheet n° 658
Rev. 15/05/2014

Category:

- Industrial detergent

Applications:

- Removes greasy dirt build-up

Strenghts:

- Specific for parts washers

High concentration detergent for parts washer, spray cleaning, ultrasonic cleaning

Applications

HB 180 is a high concentration and high cleaning power detergent specifically formulated to remove oil, grease, soot and dirt build-up from various sources. The product is particularly suitable for spray cleaning, in parts washers and in ultrasonic cleaning.

Despite being an alkaline cleaner, at the right concentrations does not damage paint, aluminum, steels, gaskets, developing a limited foam during the washing steps.

HB 180 can be used at temperatures up to 80 °C.

Directions for use

Dilute the product with water in the indicative proportion of 1:10 for persistent dirt and sludge removal, 1:20 for lighter dirt, 1:50 as degreaser for general use. Spray the product on the part to be treated and allow to react for the time required, depending on the type of contamination and the environmental conditions. Indicatively, from a few minutes to an hour.

Using the pressure washer, it is advisable to spray the diluted product, at low pressure, from the bottom upwards, then high-pressure rinse, always from bottom to top. For use in **parts washing and ultrasound machines** is recommended to follow the manufacturer's instructions. Using the same concentrations for spraying use.

Technical specifications

Product for industrial and professional use. The manufacturer declines all responsibility for any damage caused by the improper use of the product.

pH	13,0
Smell	Characteristic
Color	Colorless
Density (20°C)	1,057