



Industry Line

Scudograf

Technical Sheet n° 872
Rev. 18/01/2017

Anti-graffiti for all absorbent building surfaces

Category:

- Sacrificial anti-graffiti

Applications:

- Building surfaces protection from graffiti

Strenghts:

- Ready to use
- Avoid costly surgeries

Yield:

- From 4 to 15 m²/litro

Product for professional and industrial use. The manufacturer declines all responsibility for any damage caused by the improper use of the product.

Applications

Scudograf is a formulation based on special polymers, ready to use, intended for buildings protection from graffiti and vandalism. Scudograf creates a practically invisible sacrificial film, capable of protecting:

- marble surfaces;
- natural stones and granites
- facing bricks;
- concrete;
- concrete blocks;
- plasters, also decorated, resistant to washing with hot pressurized water;

How to use

The surfaces to be treated must be clean, cohesive and dry.

The product must be applied up to refusal, at a temperature not lower than 10°C and not higher than 35°C, using rollers, brushes or airless sprayers. Generally, a single application of the product is sufficient to obtain a good result. If a second application is required, wait at least 24 hours from the first application at a temperature of 25°C.

Warnings: Check for any chromatic variations by carrying out a test on small surfaces. Make sure that the substrates treated are clean, dry and compact.

GRAFFITI REMOVAL

To remove graffiti it is necessary to clean the surface with the Remograf product.

After removing the graffiti, it may be necessary to restore the protection by reapplying Scudograf again.

Store Scudograf at temperatures between +5 and + 35°C in the original sealed packaging. **The product is not frost-proof.**

Technical specifications

pH	9 (internal method)
Odor	Not perceptible
Color	White
Density (20°C)	1,005 g/cm ³ (metodo interno)