



Industry
Line

Sequestrol BIO/AL

Technical Sheet n° 870
Rev. 20/12/2016

Category:

- Water treatment product

Applications:

- Inhibits fouling in process and cooling water

Strenghts:

- Effective for a long time
- Suitable for cooling systems where there are aluminum pipes, valves and fittings.

Anti-encrusting dispersant for process water and cooling systems where there are aluminum pipes, valves and fittings.

Applications

Sequestrol BIO/AL is a concentrated product with anti-scaling action, dispersant for process water and cooling systems where there are aluminum pipes, valves and fittings.

Dosed regularly in the make-up water of the circuits, it keeps the salts in dispersion which would otherwise precipitate due to the increase in concentration due to recirculation and heat exchange. Suitable for systems involving large masses of water, even partially stagnant.

How to use

Sequestrol BIO/AL can be used as it is in "shots" or continuously depending on the system in which it is applied and its characteristics.

The average dosage of Sequestrol BIO/AL is proportional to the flow rate or water replenishment of the system in which the product is applied and can vary from 500 to 1000 ppm, equal to 0.5 – 1 liter every 1000 liters of conditioned water .

Warnings: For handling the product, consult the safety data sheet carefully.

Technical specifications

pH	4
Odor	Characteristic
Color	Colorless to pale yellow
Density (20°C)	1,060 g/cm ³

Product for professional and industrial use. The manufacturer declines all responsibility for any damage caused by the improper use of the product.